MAINE

Wood-effect porcelain plank · Wall & floor

Maine is a long wood-effect porcelain plank in soft natural tones for floors throughout the home.

PRODUCT OVERVIEW

Colours	Caramel, Honey, Ivory
Size (mm)	1200 × 200
Thickness	9.5 mm
Material	Through-body porcelain, EN 14411 Group BIa (unglazed)
Finish	Natural (matt)
Edge	Non-rectified

TECHNICAL CHARACTERISTICS

PROPERTY	TEST STANDARD	RESULT
Dimensions & surface quality	ISO 10545-2	Conforms
Water absorption	ISO 10545-3	≤ 0.5%
Breaking strength / modulus of rupture	ISO 10545-4	≥ 1300 N / ≥ 35 N/mm²
Deep abrasion	ISO 10545-6	≤ 175 mm³
Thermal shock resistance	ISO 10545-9	Conforms
Frost resistance	ISO 10545-12	Conforms
Household chemicals & pool salts	ISO 10545-13	Class A
Stain resistance	ISO 10545-14	Class 5
Colour fastness to light	DIN 51094	Conforms
Surface abrasion (floor use)	Manufacturer method	Class H (Honey, Ivory); Class G (Caramel)
Fire classification	96/603/EC	A1fl (floor) / A1 (wall)

SLIP RESISTANCE

TEST	TEST STANDARD	RESULT
Ramp (shod)	EN 16165 Annex B (DIN 51130)	R10
DCOF, wet	ANSI A326.3	≥ 0.42
BCRA	D.M. 236/89	> 0.40
Class (Spanish CTE)	UNE EN 16165 Annex C	Class 2
Pendulum (UK PTV)	BS EN 16165 Annex C	Not published for natural finish

Surface abrasion classes (manufacturer scale): E = any room except entrances and kitchens; F = any room without direct outside access; G = medium-heavy traffic, light commercial; H = hard wear, public and private. Values are manufacturer test data for first-quality material and are typical for the range. Tile colours shown in print or on screen are for guidance only, so please request a sample. Check shade, calibre and quality before fixing: no claims can be accepted for tiles once installed. Follow BS 5385 and the adhesive and grout manufacturers' guidance.