PURE

Marble-effect porcelain · Wall & floor

Pure is a soft, colourful onyx-effect porcelain in matt and polished finishes.

PRODUCT OVERVIEW

Colours	Blue, Green, Honey, Perla, Pink
Size (mm)	1200 × 600
Thickness	9 mm
Material	Glazed porcelain stoneware, EN 14411 Group Bla GL
Finish	Matt (silk) or polished
Edge	Rectified

TECHNICAL CHARACTERISTICS

PROPERTY	TEST STANDARD	RESULT
Dimensions & surface quality	ISO 10545-2	Conforms (rectified)
Water absorption	ISO 10545-3	≤ 0.5%
Breaking strength	ISO 10545-4	≥ 1300 N
Modulus of rupture	ISO 10545-4	≥ 35 N/mm²
Surface abrasion (traffic class)	Manufacturer method	Matt: HT (heavy traffic); polished: MT (medium traffic)
Crazing resistance	ISO 10545-11	Conforms
Thermal shock resistance	ISO 10545-9	Conforms
Frost resistance	ISO 10545-12	Conforms
Household chemicals	ISO 10545-13	Class A
Acids & alkalis, low / high concentration	ISO 10545-13	LA–LB / HA–HB
Stain resistance	ISO 10545-14	Class 5
Colour fastness to light	DIN 51094	Conforms
Fire classification	EN 13501-1	A1fl / A1

SLIP RESISTANCE

TEST	TEST STANDARD	RESULT
Ramp (shod)	EN 16165 Annex B (DIN 51130)	R10
Barefoot ramp	EN 16165 Annex A (DIN 51097)	Class A+B
Pendulum, wet (sliders 96 & 55)	BS EN 16165 Annex C	> 36 (low slip potential)
DCOF, wet	ANSI A326.3	≥ 0.50
BCRA	D.M. 236/89	> 0.40

Slip ratings apply to the matt finish only. No slip rating is published for the polished finish; use it on walls and dry floors. Values are manufacturer test data for first-quality material and are typical for the range. Tile colours shown in print or on screen are for guidance only, so please request a sample. Check shade, calibre and quality before fixing: no claims can be accepted for tiles once installed. Follow BS 5385 and the adhesive and grout manufacturers' guidance.